

PRODUCTION OF OXAZOLINE POLYMER/SILICA COMPOSITE MOLDED ARTICLE**Publication number:** JP3056535**Publication date:** 1991-03-12**Inventor:** SAEGUSA TAKEO; NAKAJO YOSHIKI; KURE SHIGEO**Applicant:** SAEGUSA TAKEO**Classification:****- International:** C08J5/18; C08G73/02; C08G77/42; C08L79/02; C08L83/04; C08J5/18; C08G73/00; C08G77/00; C08L79/00; C08L83/00; (IPC1-7): C08G73/02; C08G77/42; C08J5/18; C08L79/02; C08L83/04**- european:****Application number:** JP19890190446 19890725**Priority number(s):** JP19890190446 19890725**Report a data error here****Abstract of JP3056535**

PURPOSE:To obtain the subject uniform and transparent composite molded article without troubles at a low cost by gelatinizing an oxazoline polymer containing hydrolyzable and polymerizable silyl group and a hydrolyzable and polymerizable silane and forming the components before or after the gelatinization. **CONSTITUTION:**An oxazoline polymer containing hydrolyzable and polymerizable group (preferably trialkoxysilyl group) and a hydrolyzable and polymerizable silane (preferably tetraalkoxy-silane) are gelatinized by co-hydrolytic polymerization reaction. Before or after the gelatinization, the components are formed in a proper form such as fiber, film or sphere to obtain the objective composite molded article having easily controllable pore diameter and its distribution. The above forming process is preferably coating.

Data supplied from the esp@cenet database - Worldwide